

MODEL 211
MY 2007, AMG and diesel models only

Passenger cars Model Year 2007
USA

Model 211



Customer: _____ Repair order number: _____

First visit	at 1,000 - 3,000 miles	Performed	YES ☐	NO ☐
-------------	------------------------	-----------	------------------------------	-----------------------------

Tire Rotation (non staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES ☐	NO ☐
---	--	---------------	------------------------------	-----------------------------

Tire Inspection (staggered and non-staggered width wheel setup)	Inspect tires for damage and correct tire inflation pressure	Tires inspected	YES ☐	NO ☐
--	--	-----------------	------------------------------	-----------------------------

Current mileage reading: _____ Oil grade/viscosity: _____


Additional notes: _____




Service work to be performed as advised by service advisor:	Completion date:	Confirm work has been performed by signing below:



US Service 1-11 and 15-20 apply to "Additional work" items only.
Vehicle determines need for US Service 12 (Engine oil and filter change) as well as US Service 13 or US Service 14
Perform each service as described.

Completed ☒		Not OK ↓	
US Service 1	not applicable		
US Service 2 Required	every 40,000 mi or 4 years: Engine compartment ☐ Replace engine air-cleaner insert	Engine 156: Engine 642:	AP09.10-P-0980TMG AP09.10-P-0980TI
US Service 3 Required	every 30,000 mi or 2 years: Engine compartment ☐ Replace combination filter		AP83.00-P-8384T
US Service 4	not applicable		
US Service 5 Required	every 150,000 mi or 15 years: Passenger compartment ☐ Replace fuel filter	Engine 156	AP47.20-P-0780TC
US Service 5 Required	every 20,000 mi or 2 years: Engine compartment ☐ Replace fuel filter	Engine 642	AP47.20-P-0780TI
US Service 6	not applicable		
US Service 7 Required	every 60,000 mi or 5 years: Engine compartment ☐ Replace spark plugs	Engine 156	AP15.10-P-1580TMG
US Service 8 Required	every 150,000 mi or 15 years: Engine compartment ☐ Replace coolant	Engine 156:	AP20.00-P-2080DA

US Service 9 Required	every 2 years: Engine compartment ☐ Replace brake fluid		AP42.00-P-4280T
US Service 9 Recommended	every 2 years: ☐ Check body for paint damage by service advisor Underside of vehicle ☐ Chassis and load-bearing body components: Check for damage and corrosion by service advisor	☐	AP98.00-P-9850BA ☐ AP00.20-P-0090BA
US Service 10 Recommended	every 5 years: Interior ☐ Tilt/sliding roof: Clean slide rails and slide shoes		AP77.20-P-7731A
US Service 11 Recommended	every 3 years: Interior ☐ Panorama sliding roof: Clean and lubricate guide mechanism		AP77.20-P-7732PB
US Service 12 Recommended	every 10,000 mi or 1 year: Engine compartment ☐ Engine oil and filter change	Engine 156: Engine 642	AP18.00-P-0101TMG AP18.00-P-0101TI
US Service 13 ↓	first at 10,000 mi or 1 year; US Service 14 ↓	after first every 20,000 mi or 2 years after first every 20,000 mi or 2 years Not OK ↓	
 Engine compartment - Required ☐ Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order Inspect poly-V-belt for damage ☐ Engine 156 ☐ Engine 642 ☐ Check catch, safety catch and hinges on engine hood for proper operation. Check fluid level, correct as required i If there is a loss of fluid, determine cause and perform repair via separate work order ☐ Brake system ☐ Power steering ☐ Windshield washer system (incl. summer/winter cleanser)			
 ☐ ☐ Reset service indicator in instrument cluster Function test ☐ ☐ Audible warning system ☐ ☐ Check parking brake (function test only)			
 Interior - Recommended Function test			

☐ ☐	☐ Warning/indicator lamps, illumination and interior lighting ☐ Windshield washer system, incl. rear window washer (where applicable), headlamp cleaning system ☐ Check safety belts and buckles for signs of external damage and function	☐ ☐ AP82.30-P-8252T ☐ AP91.40-P-9150M																				
Wheels, brakes - Required																						
 ☐ ☐	☐ Check thickness of brake pads, front and rear ☐ Correct tire inflation pressure and enter in bar or psi. LF RF L R RR bar/psi: _____	☐ AP42.10-P-4253A ☐																				
Wheels, brakes - Recommended																						
 ☐	☐ Remove and install wheels ☐ Inspect tires for damage and splits, measure tread depth, enter in mm: <table style="width: 100%; border-collapse: collapse; margin-top: 5px;"> <thead> <tr> <th></th> <th style="text-align: center;">LF</th> <th style="text-align: center;">RF</th> <th style="text-align: center;">LR</th> <th style="text-align: center;">RR</th> </tr> </thead> <tbody> <tr> <td style="text-align: right;">outside</td> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> <tr> <td style="text-align: right;">center</td> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> <tr> <td style="text-align: right;">inside</td> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> </tbody> </table>		LF	RF	LR	RR	outside	_____	_____	_____	_____	center	_____	_____	_____	_____	inside	_____	_____	_____	_____	☐ AP40.10-P-4050Z ☐ AP40.10-P-4051Z
	LF	RF	LR	RR																		
outside	_____	_____	_____	_____																		
center	_____	_____	_____	_____																		
inside	_____	_____	_____	_____																		
Underside of vehicle - Required																						
	☐ Leakage - Major components Check for chafe marks, line routing, damaged components ☐ In the event of leakage, determine cause and perform repair via separate work order ☐ Check front axle ball joints for play, check rubber boots ☐ Inspect condition of driveshaft flexible discs ☐ Inspect play of tie rod and drag link joints, inspect rubber boots	☐ AP00.20-P-0053BA ☐ AP33.20-P-3353BA ☐ AP41.10-P-4152Z ☐ AP46.00-P-4653F																				
Trunk - Recommended																						
 ☐ ☐ ☐	☐ Check trunk lighting ☐ Check battery condition using "Midtronics MCR 717" Tester. Attach Midtronics MCR 717 Test Report print out here. ☐ Check TIREFIT sealant expiration date and enter here _____ If necessary replace TIREFIT subject to a separate repair order (AMG wagons with third row seat only)	☐ ☐ AP54.10-U-5453A ☐ AP40.10-P-4054R																				
Vehicle front/rear - Recommended																						
 ☐	☐ Check, correct headlamp setting ☐ Check wiper blade condition	☐ AP82.10-P-8260T ☐ AP82.30-P-8253G																				
Completed ☒		Not OK ↓																				

US Service 15 - 19	not applicable	
US Service 20 Required	once at 40,000 mi: Underside of vehicle	
	☐ Automatic transmission - Oil and filter change	AP27.00-P-2702W