

MODEL 211
MY 2008, except AMG and diesel models

Passenger cars Model Year 2008
USA

Model 211



Customer: _____ **Repair order number:** _____

First visit	at 1,000 - 3,000 miles	Performed	YES	☐	NO	☐
--------------------	-------------------------------	------------------	------------	--------------------------	-----------	--------------------------

Tire Rotation (non staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES	☐	NO	☐
--	---	----------------------	------------	--------------------------	-----------	--------------------------

Tire Inspection (staggered and non-staggered width wheel setup)	Inspect tires for damage and correct tire inflation pressure	Tires inspected	YES	☐	NO	☐
---	---	------------------------	------------	--------------------------	-----------	--------------------------

Current mileage reading: _____ **Oil grade/viscosity:** _____




Additional notes: _____

Service work to be performed as advised by service advisor:	Completion date:	Confirm work has been performed by signing below:
--	-------------------------	--



US Service 1-11 and 15-20 apply to "Additional work" items only.
 Vehicle determines need for US Service 12 (Engine oil and filter change) as well as US Service 13 or US Service 14.
 Perform each service as described.

Completed ☒		Not OK ☐	
	↓		↓
US Service 1	Not applicable		
US Service 2 Required	every 52,000 mi or 4 years: Engine compartment ☐ Replace engine air-cleaner insert Engines 272, 273 AP09.10-P-0980TS		
US Service 3 Required	every 26,000 mi or 2 years: Engine compartment ☐ Replace combination filter AP83.00-P-8384T		
US Service 4	Not applicable		
US Service 5 Required	every 143,000 mi or 15 years: Passenger compartment ☐ Replace fuel filter Engines 272, 273 AP47.20-P-0780TC		
US Service 6	Not applicable		
US Service 7 Required	every 91,000 mi or 5 years: Engine compartment ☐ Replace spark plugs Engines 272, 273 AP15.10-P-1580TS		
US Service 8 Required	every 143,000 mi or 15 years: Engine compartment ☐ Replace coolant Engines 272, 273 AP20.00-P-2080DA		
US Service 9 Required	every 2 years: Engine compartment ☐ Replace brake fluid AP42.00-P-4280T		
US Service 9 Recommended	every 2 years: ☐ Check body for paint damage by service advisor ☐ AP98.00-P-9850BA		

☐ ☐	☐ Check thickness of brake pads, front and rear ☐ Correct tire inflation pressure and enter in bar or psi. LF RF L R RR bar/psi: _____	☐ AP42.10-P-4253A ☐															
Wheels, brakes - Recommended																	
 ☐	☐ Inspect tires for damage and splits, measure tread depth, enter in mm: LF RF LR RR <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">outside</td> <td style="width: 20%; border-bottom: 1px solid black;"></td> <td style="width: 20%; border-bottom: 1px solid black;"></td> <td style="width: 20%; border-bottom: 1px solid black;"></td> <td style="width: 20%; border-bottom: 1px solid black;"></td> </tr> <tr> <td>center</td> <td style="border-bottom: 1px solid black;"></td> <td style="border-bottom: 1px solid black;"></td> <td style="border-bottom: 1px solid black;"></td> <td style="border-bottom: 1px solid black;"></td> </tr> <tr> <td>inside</td> <td style="border-bottom: 1px solid black;"></td> <td style="border-bottom: 1px solid black;"></td> <td style="border-bottom: 1px solid black;"></td> <td style="border-bottom: 1px solid black;"></td> </tr> </table>	outside					center					inside					☐ AP40.10-P-4051Z
outside																	
center																	
inside																	
Underside of vehicle - Required																	
 ☐	☐ Leakage - Major components Check for chafe marks, line routing, damaged components ☐ In the event of leakage, determine cause and perform repair via separate work order ☐ Check front axle ball joints for play, check rubber boots ☐ Inspect condition of flexible discs ☐ Inspect play of tie rod and drag link joints, inspect rubber boots	☐ AP00.20-P-0053BA ☐ AP33.20-P-3353BA ☐ AP41.10-P-4152Z ☐ AP46.00-P-4653F															
Vehicle front/rear - Recommended																	
 ☐	☐ Check, correct headlamp setting ☐ Check wiper blade condition	☐ AP82.10-P-8260T ☐ AP82.30-P-8253G															
Trunk - Required																	
 ☐	☐ Correct inflation pressure in spare tire and enter in bar or psi. bar/psi: _____	☐															
Trunk - Recommended																	
 ☐ ☐ ☐	☐ Check trunk lighting ☐ Battery, check and correct fluid level ☐ Check battery condition using "Midtronics MCR 717" Tester. Attach Midtronics MCR 717 Test Report print out here.	☐ ☐ AP54.10-P-5410A ☐ AP54.10-U-5453A															
Completed ☒		Not OK															
↓		↓															
US Service 15 - 19	not applicable																
US Service 20 Required	once at 39,000 mi: Underside of vehicle ☐ Automatic transmission - Oil and filter change Transmission 722.6 Transmission 722.9 ☐ Transfer case - oil change (4MATIC models)	AP27.00-P-2702I AP27.00-P-2702W AP28.00-P-2801P															