MODEL 211

MY 2008, AMG and Diesel models only

Passenger cars Model Year 2008

USA

Model 211



Customer:		Repair order number:			
First visit	at 1,000 - 3,000 miles	Performed	YES		NO
Tire Rotation (non staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES		NO
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for damage and correct tire inflation pressure	Tires inspected	YES		NO
Current mileage reading:		Oil grade/viscosity:			
Additional notes:					
Service work to be performed as advised by Completion date: service advisor:		Confirm work has been performed by signing below:			
[:					

•
11

US Service 1-11 and 15-20 apply to "Additional work" items only.

Vehicle determines need for US Service 12 (Engine oil and filter change) as well as US Service 13 or US Service 14 Perform each service as described.

Completed ⊠			Not OK		
	\downarrow		↓		
US Service 1	not applicable				
US Service 2 Required	every 40,000 mi or 4 years: Engine compartment				
	Replace engine air-cleaner insert	Engine 156:	AP09.10-P-0980TMG		
		Engine 642:	AP09.10-P-0980TI		
US Service 3 Required	every 30,000 mi or 2 years: Engine compartment				
-	Replace combination filter		AP83.00-P-8384T		
US Service 4	not applicable				
US Service 5 Required	every 150,000 mi or 15 years: Passenger compartment				
•	Replace fuel filter	Engine 156	AP47.20-P-0780TC		
US Service 5 Required	every 20,000 mi or 2 years: Engine compartment				
Required	Replace fuel filter	Engine 642	AP47.20-P-0780TI		
US Service 6	not applicable				
US Service 7	every 60,000 mi or 5 years:				
Required	Engine compartment				
	Replace spark plugs	Engine 156	AP15.10-P-1580TMG		
US Service 8	every 150,000 mi or 15 years:				
Required	Engine compartment Replace coolant	Engine 156:	AP20.00-P-2080TMG		

			Engine 642:		AP20.00-P-2080BA
US Service 9		every 2 years:			
Required		Engine compartment			AB40.00 B 4000T
		Replace brake fluid			AP42.00-P-4280T
US Service 9		every 2 years:			
Recommended	_	Charle hade for point domage	r	_	4 D00 00 D 0050D4
	Ш	Check body for paint damage by service advisor	L		AP98.00-P-9850BA
		Underside of vehicle			
	П	Chassis and load-bearing body components:]		AP00.20-P-0090BA
		Check for damage and corrosion			
IIC Comice 40		by service advisor			
US Service 10 Recommended		every 5 years: Passenger compartment			
	П	T11/ 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			AP77.20-P-7731A
		shoes			
US Service 11 Recommended		every 3 years: Passenger compartment			
Recommended		Panorama sliding roof: Clean and lubricate			AP77.20-P-7732PB
		guide mechanism			74 77.20 7 77027 8
US Service 12		every 10,000 mi or 1 year:			
Recommended	_	Engine compartment Engine oil and filter change	Engine 156:		AP18.00-P-0101TMG
	Ш	Engine on and liner change	· ·		
IIC Comdos		first at 40 000 miles 4 vecan	Engine 642	—	AP18.00-P-0101TI
US Service 13		first at 10,000 mi or 1 year;	after first every 20,000 mi or 2 years		
US Serv		first at 20,000 mi or 2 years;			
	14		after first every 20,000 mi or 2 years		
V	\		Not O	<	
			,	<u>/</u>	
_		Engine compartment - Required			
	٦				
	3				
	_	Laskaga Major componento	-	_	4 D00 00 D 0050D4
	\circ	Leakage - Major components Check for chafe marks, line routing, damaged	L		AP00.20-P-0053BA
		components			
		in the event of leakage, determine cause			
		and perform repair via separate work order			
	_	Inspect poly-V-belt for damage	_	_	
	0	Engine 156	L	┙	AP13.22-P-1352TS
	0	Engine 642	[AP13.22-P-1352TI
	0	Check catch, safety catch and hinges on	[AP88.40-P-8851T
	_	engine hood for proper operation.			A D 47 00 D 070 4 A
	\circ	Drain fuel filter (Engine 642)			AP47.20-P-0794A
		Check fluid level, correct as required			
		ilf there is a loss of fluid, determine cause and perform repair via separate work order			
	\cap	Brake system	Г	7	AP42.10-P-4210Z
		Power steering	Engine 450.	_	
	O	rower steering	Engine 156:	_	AP46.00-P-4611BB
_	_	M/s dahiald wash as seed as	Engine 642:		AP46.00-P-4611P
	\circ	Windshield washer system (incl. summer/winter cleanser)			AP82.35-P-8210N
		Interior - Required			
		•			
	3				
	0	Reset service indicator in instrument cluster			AP00.20-P-0042TA
	0	Check parking brake (function test only)]		
		Interior - Recommended		_	
	3				
		Function test			
	0	Horn]		

	 Warning/indicator lamps, illumination and interior lighting 	AP54.30-P-5452C
	Windshield washer system, incl. rear window	☐ AP82.30-P-8252A
	washer (where applicable), headlamp cleaning system	
	Check safety belts and buckles for signs of	☐ AP91.40-P-9150M
	external damage and function Wheels, brakes - Required	
	,	
	3	
† †	Check thickness of brake pads,	☐ AP42.10-P-4253A
Ш	front and rear	AF42.10-F-4233A
	Correct tire inflation pressure and enter in bar or psi.	
	LF RF	
	L R	
	RR bar/psi:	
	Wheels, brakes - Recommended	
	Inspect tires for damage and splits, measure	☐ AP40.10-P-4051Z
	tread depth, enter in mm: LF RF LR RR	
	outside	
	inside	
	Underside of vehicle - Required	
	ב	
	Check for chofe marks line routing demand	☐ AP00.20-P-0053BA
	Check for chafe marks, line routing, damaged components	
	In the event of leakage, determine cause and perform repair via separate work order	
	Check front axle ball joints for play, check	☐ AP33.20-P-3353BA
	rubber boots Inspect condition of driveshaft flexible discs	☐ AP41.10-P-4152Z
	Inspect play of tie rod and drag link joints,	☐ AP46.00-P-4653F
	inspect rubber boots	
	Trunk - Recommended	
	Check trunk lighting	
	Battery, check and correct fluid level	AP54.10-P-5410A
	Check battery condition using "Midtronics MCR 717" Tester.	☐ AP54.10-U-5453A
	Attach Midtronics MCR 717 Test Report print out here.	
	Check TIREFIT sealant expiration date and	AP40.10-P-4054R
	enter here If necessary replace TIREFIT subject to a	
	separate repair order (AMG wagons with third row seat only)	
	Vehicle front/rear - Recommended	
÷	_ ,	
160-11-0-	=)	
	Check, correct headlamp setting	☐ AP82.10-P-8260T
	Check wiper blade condition	☐ AP82.30-P-8253G
Complete		Not OK
Copior		\downarrow

US Service 15 - 19	not applicable	
US Service 20 Required	once at 40,000 mi: Underside of vehicle	
	Automatic transmission - Oil and filter change	AP27.00-P-2702W