

MODEL 211
MY 2009

Model Year 2009
USA

Model 211



Customer: _____

Repair order number: _____

Tire Rotation
(non-staggered width
wheel setup only)

A 5,000-mile recommended tire rotation interval will likely necessitate tire rotation at least once in between each 10,000-mile maintenance service and at every 10,000-mile maintenance service.

Tires rotated **YES** ☐ **NO** ☐

[i] Note: For any condition found while performing the checks or inspections included in this maintenance sheet, determine the cause and perform the repair using a separate repair order.

Current mileage reading: _____

Oil grade/viscosity: _____

Additional notes: _____

Service work to be performed as advised by service advisor:

Completion date:

Confirm work has been performed by signing below:

Required Service Work	at 2,000 miles	
☒ Performed (check if performed)		
☐ Rear axle differential fluid replacement	(only E 63 AMG with AMG performance package)	
Required Service Work	at 10,000 miles or 1 year; then every 20,000 miles or 2 years	
[i] Plus any applicable additional work listed at the end of this service sheet		
☒ Performed (check if performed)		Not OK ↓
☐ Reset maintenance service indicator in instrument cluster		AP00.20-P-0042TA
☐ Engine - oil and filter change		
Engine 272, 273		AP18.00-P-0101TS
Engine 156		AP18.00-P-0101TMG
Engine 642		AP18.00-P-0101TI
☐ Check catch, safety catch and hinges on engine hood for proper operation		☐ AP88.40-P-8851T
Check the following fluid levels, correct if necessary		
☐ Check coolant level		☐ AH20.00-P-1142-01V

☐ Brake system	☐ AP42.10-P-4210Z
☐ Power steering ☐ The fluid level must always be on the maximum mark, corresponding to the oil temperature. Engine 272, 273, 156 Engine 642	☐ AP46.00-P-4611BB ☐ AP46.00-P-4611P
☐ Windshield washer system	☐ AP82.35-P-8210N
☐ Check thickness of brake pads, front and rear	☐ AP42.10-P-4253A
☐ Correct tire inflation pressure and enter in bar or psi: LF RF LR RR bar/psi: _____	☐
☐ Check inflation pressure in spare tire (if applicable) and enter in bar or psi: bar/psi: _____	☐
☐ Reminder: Reset maintenance service indicator in instrument cluster	AP00.20-P-0042TA
Recommended Service Work at 10,000 miles or 1 year; then every 20,000 miles or 2 years	
☒ Performed (check if performed)	Not OK ↓
Check the following fluid levels, correct if necessary	
☐ Main or starter battery	☐ AP54.10-P-5410A
Electrical system checks	
☐ Horn, high beam flasher, hazard warning flasher, turn signals	☐
☐ Warning/indicator lamps, illumination and interior lighting/exterior lighting	☐ AP54.30-P-5452C
☐ Check trunk/cargo area lighting	☐
☐ Battery (main/starter/auxiliary) check condition using "Midtronics MCR 717" tester. Attach Midtronics MCR 717 Test Report print out here	☐ AP54.10-U-5453A
Visual and functional checks	
☐ Check windshield washer and headlamp cleaning system	☐ AP82.30-P-8252A
Tire checks	
☐ Tire rotation (where applicable)	
☐ Inspect tires for damage, measure thread depth and enter in mm: LF RF LR RR outside _____ center _____ inside _____	☐ AP40.10-P-4051Z
☐ Check TIREFIT tire sealant expiration date (where applicable)	☐ AP40.10-P-4054R
☐ Activate Tire Pressure Monitoring System; Refer to vehicle Operator's Manual	
Chassis checks	
☐ Visually check brake system components, lines, hoses, calipers	☐
☐ Check thickness of brake pads and discs, front and rear wheels removed Pads Discs	☐ AP42.10-P-4253A ☐ AP42.10-P-4258R
☐ Replace wiper blades	
Required Service Work at 20,000 miles or 2 years; then every 20,000 miles or 2 years	
☐ Plus any applicable additional work listed at the end of this service sheet	
☒ Performed (check if performed)	Not OK ↓

☐ Reset maintenance service indicator in instrument cluster	AP00.20-P-0042TA
☐ Engine - oil and filter change Engine 272, 273 Engine 156 Engine 642	AP18.00-P-0101TS AP18.00-P-0101TMG AP18.00-P-0101TI
☐ Check catch, safety catch and hinges on engine hood for proper operation	☐ AP88.40-P-8851T
☐ Check condition of poly-V-belt Engine 272, 273, 156 Engine 642	☐ AP13.22-P-1352TS ☐ AP13.22-P-1352TI
☐ Replace fuel filter Engine 642	AP47.20-P-0780TI
☐ Replace brake fluid	AP42.00-P-4280T
Check the following fluid levels, correct if necessary	
☐ Check coolant level	☐ AH20.00-P-1142-01V
☐ Brake system	☐ AP42.10-P-4210Z
☐ Power steering ☐ The fluid level must always be on the maximum mark, corresponding to the oil temperature. Engine 272, 273, 156 Engine 642	☐ AP46.00-P-4611BB AP46.00-P-4611P
☐ Windshield washer system	☐ AP82.35-P-8210N
Function check	
☐ Parking brake (function test only)	☐
☐ Replace combination filter	AP83.00-P-8384T
☐ Check thickness of brake pads, front and rear	☐ AP42.10-P-4253A
☐ Correct tire inflation pressure and enter in bar or psi: LF RF LR RR bar/psi:	☐
☐ Check inflation pressure in spare tire (if applicable) and enter in bar or psi: bar/psi:	☐
☐ Leakage - Major components Check underbody and engine compartment for chafe marks, line routing, damaged components.	☐ AP00.20-P-0053BA
☐ Visually inspect condition of front axle ball joints, rubber boots	☐
☐ Visually inspect condition of driveshaft flexible discs	☐ AP41.10-P-4152Z
☐ Visually inspect condition of steering mechanical components, rubber boots	☐
☐ Reminder: Reset maintenance service indicator in instrument cluster	AP00.20-P-0042TA
Recommended Service Work	at 20,000 miles or 2 years; then every 20,000 miles or 2 years
☒ Performed (check if performed)	Not OK ↓
Check the following fluid levels, correct if necessary	
☐ Main or starter battery	☐ AP54.10-P-5410A
Electrical system checks	
☐ Horn, high beam flasher, hazard warning flasher, turn signals	☐
☐ Warning/indicator lamps, illumination and interior lighting/exterior lighting	☐ AP54.30-P-5452C
☐ Check trunk/cargo area lighting	☐
☐ Check and correct headlamp setting	☐ AP82.10-P-8260T

☐ Battery (main/starter/auxiliary) check condition using "Midtronics MCR 717" tester. Attach Midtronics MCR 717 Test Report print out here	☐ AP54.10-U-5453A												
Visual and functional checks													
☐ Check seat belts and buckles for signs of external damage and proper function	☐ AP91.40-P-9150M												
☐ Check windshield washer and headlamp cleaning system	☐ AP82.30-P-8252A												
☐ Check, clean, and lubricate tilt/sliding roof mechanism (where applicable)	☐ AP77.20-P-7731A												
☐ Check, clean, and lubricate panoramic roof mechanism (where applicable)	☐ AP77.20-P-7732PB												
☐ Check bodywork for paintwork damage	☐ AP98.00-P-9850BA												
Tire checks													
☐ Tire rotation (where applicable)													
☐ Inspect tires for damage, measure thread depth and enter in mm: LF RF LR RR <table style="width: 100%; border-collapse: collapse; margin-top: 5px;"> <tr> <td style="width: 25%;">outside</td> <td style="width: 25%; border-bottom: 1px solid black;"></td> <td style="width: 25%; border-bottom: 1px solid black;"></td> <td style="width: 25%; border-bottom: 1px solid black;"></td> </tr> <tr> <td>center</td> <td style="border-bottom: 1px solid black;"></td> <td style="border-bottom: 1px solid black;"></td> <td style="border-bottom: 1px solid black;"></td> </tr> <tr> <td>inside</td> <td style="border-bottom: 1px solid black;"></td> <td style="border-bottom: 1px solid black;"></td> <td style="border-bottom: 1px solid black;"></td> </tr> </table>	outside				center				inside				☐ AP40.10-P-4051Z
outside													
center													
inside													
☐ Check TIREFIT tire sealant expiration date (where applicable)	☐ AP40.10-P-4054R												
☐ Activate Tire Pressure Monitoring System; Refer to vehicle Operator's Manual													
Chassis checks													
☐ Visually check brake system components, lines, hoses, calipers	☐												
☐ Check thickness of brake pads and discs, front and rear wheels removed Pads Discs	☐ AP42.10-P-4253A ☐ AP42.10-P-4258R												
☐ Check chassis and load-bearing body components for damage and corrosion	☐ AP00.20-P-0090SX												
☐ Replace wiper blades													
High Mileage Additional Work													
☒ Performed (check if performed)													
☐ Replace fuel filter Engine 272, 273, 156	If more than 150,000 mi or 15 years since last replacement ☐ AP47.20-P-0780TC												
☐ Replace coolant Engine 272, 273 Engine 156 Engine 642	If more than 150,000 mi or 15 years since last replacement If more than 150,000 mi or 15 years since last replacement If more than 150,000 mi or 15 years since last replacement ☐ AP20.00-P-2080DA ☐ AP20.00-P-2080TMG ☐ AP20.00-P-2080BA												
☐ Automatic transmission - oil and filter change	If more than 40,000 mi or 4 years since last replacement ☐ AP27.00-P-2702W												
☐ Rear axle differential fluid replacement (only E 63 AMG with AMG performance package)	If more than 40,000 mi or 4 years since last replacement												
☐ Transfer case - oil change (4MATIC models)	Once at 40,000 mi or 4 years ☐ AP28.00-P-2801P												
☐ Replace air filter Engine 272, 273 Engine 156 Engine 642	If more than 40,000 mi or 4 years since last replacement If more than 40,000 mi or 4 years since last replacement If more than 40,000 mi or 4 years since last replacement ☐ AP09.10-P-0980TS ☐ AP09.10-P-0980TMG ☐ AP09.10-P-0980TI												
☐ Replace spark plugs Engine 272, 273 Engine 156	If more than 80,000 mi or 8 years since last replacement If more than 80,000 mi or 8 years since last replacement ☐ AP15.10-P-1580TS ☐ AP15.10-P-1580TMG												